

C8.IT

Ceiling mounted, two-way vented enclosure

features

- ▶ Two-way high performance flush mounting ceiling speaker
- ▶ 8" (200mm) UL94V-0 carbon fibre loaded polypropylene cone bass
- ▶ Wide dispersion – 90° conical up to 7kHz
- ▶ High & low impedance operation – transformer included
- ▶ 110dB max SPL @ 1 metre (16 ohm)
- ▶ 125 watt power handling (60W through transformer)
- ▶ Polyswitch and thermal fuse protected
- ▶ Steel backcan


applications

- ▶ Fixed installs in ceilings & walls
- ▶ Bars and restaurants

The C8.IT has been specifically designed for higher ceilings where its high SPL capability and controlled 90° dispersion enable it to provide excellent intelligibility in more reverberant rooms. It features an 8" (200mm) unit with a carbon fibre loaded, polypropylene cone and a 1" (25mm) horn-loaded dome tweeter mounted side-by-side for optimum dispersion and smooth response off-axis. The enclosure is ported to extend the low frequency performance and the 5-point mounting system ensures that installation is fast and secure. Input and link terminals make paralleling units a simple operation and a steel cover plate protects the input connector against fire.

These products comply with UL2043 Fire Tests for Heat & Visible Smoke Release for Discrete Products and their Accessories Installed in Air Handling Spaces. Listed ULI480 General Signalling Speakers. SUITABLE FOR USE IN AIR HANDLING SPACES

overall dimensions



C8.IT



technical specifications

TYPE	Ceiling mounted, two-way vented enclosure
FREQUENCY RESPONSE (1)	80Hz-18kHz ± 3dB -10dB @ 50Hz
DRIVERS	8" (200mm) UL94V-0 PP bass driver 1" (25mm) dome tweeter
RATED POWER (2)	125W AES, 500W peak
SENSITIVITY (3)	91dB
MAXIMUM SPL (4)	110dB continuous, 116dB peak
NOMINAL IMPEDANCE	16 ohms
DISPERSION (-6dB)	90° conical up to 7kHz
CROSSOVER	3kHz passive
ENCLOSURE	Steel backcan
FINISH	Bezel & grille – white UV resistant Overpaintable Backcan – zinc plated
PROTECTIVE GRILLE	Perforated steel
CONNECTORS	Rising clamp plug and socket
ACCESSORIES (included)	60W 70/100V line transformer Tile rails C bracket Paint mask Cut-out template
VOLTAGE TAPS	100V – 60W, 30W, 15W 70V – 60W, 30W, 15W, 7.5W
DIMENSIONS	(OD) 354mm x (D) 258mm (OD) 13.9ins x (D) 10.2ins
CUT-OUT DIAMETER	308mm (12.14ins)
WEIGHT	6.7kg (14.8lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.



www.martin-audio.com